

CIRCULAR HOLLOW SECTION



Circular Size Range
21.3mm to 406.4mm

Thickness
1.6mm to 12mm

CIRCULAR HOLLOW SECTION IS:1161 : 2014										
Outside Diameter	Thickness	Mass	Area of Cross Section	Internal Volume	Moment of Inertia	Elastic Modulus	Plastic Modulus	Radius of Gyration	Square of Radius of Gyration	Torsional Constant
mm	mm	kg/m	cm ²	cm ³ /m	cm ⁴	cm ³	cm ³	cm	cm ²	cm ³
21.3	1.6	0.78	0.99	257	0.48	0.45	0.62	0.70	0.49	0.91
21.3	1.8	0.87	1.10	246	0.53	0.50	0.69	0.69	0.48	0.99
21.3	2.0	0.95	1.21	235	0.57	0.54	0.75	0.69	0.47	1.07
21.3	2.2	1.04	1.32	224	0.61	0.57	0.81	0.68	0.46	1.15
21.3	2.5	1.16	1.48	209	0.66	0.62	0.89	0.67	0.45	1.25
21.3	2.8	1.28	1.63	194	0.71	0.67	0.97	0.66	0.44	1.34
26.4	1.6	0.98	1.25	423	0.96	0.73	0.99	0.88	0.77	1.46
26.4	1.8	1.09	1.39	408	1.06	0.80	1.09	0.87	0.76	1.60
26.4	2.0	1.20	1.53	394	1.15	0.87	1.19	0.87	0.75	1.74
26.4	2.2	1.31	1.67	380	1.23	0.94	1.29	0.86	0.74	1.87
26.4	2.5	1.47	1.88	360	1.35	1.03	1.43	0.85	0.72	2.05
26.4	2.8	1.63	2.08	340	1.47	1.11	1.57	0.84	0.71	2.22
33.7	1.6	1.27	1.61	731	2.08	1.24	1.65	1.14	1.29	2.47
33.7	1.8	1.42	1.80	712	2.30	1.37	1.83	1.13	1.28	2.73
33.7	2.0	1.56	1.99	693	2.51	1.49	2.01	1.12	1.26	2.98
33.7	2.2	1.71	2.18	674	2.71	1.61	2.19	1.12	1.25	3.22
33.7	2.5	1.92	2.45	647	3.00	1.78	2.44	1.11	1.22	3.56
33.7	2.8	2.13	2.72	620	3.27	1.94	2.68	1.10	1.20	3.88
33.7	3.2	2.41	3.07	585	3.60	2.14	2.99	1.08	1.18	4.28
33.7	3.6	2.67	3.40	552	3.91	2.32	3.28	1.07	1.15	4.64
38.1	3.2	2.75	3.51	789	5.39	2.83	3.91	1.24	1.54	5.66
38.1	3.6	3.06	3.90	750	5.87	3.08	4.30	1.23	1.50	6.16
38.1	4.0	3.36	4.29	712	6.31	3.31	4.67	1.21	1.47	6.63
38.1	4.5	3.73	4.75	665	6.82	3.58	5.11	1.20	1.44	7.16
38.1	5.0	4.08	5.20	620	7.28	3.82	5.52	1.18	1.40	7.65
38.1	6.0	4.75	6.05	535	8.07	4.23	6.25	1.15	1.33	8.47
38.1	8.0	5.94	7.56	384	9.17	4.82	7.42	1.10	1.21	9.63
42.4	1.6	1.61	2.05	1207	4.27	2.02	2.66	1.44	2.08	4.03
42.4	1.8	1.80	2.30	1182	4.74	2.24	2.97	1.44	2.06	4.47
42.4	2.0	1.99	2.54	1158	5.19	2.45	3.27	1.43	2.05	4.90
42.4	2.3	2.27	2.90	1122	5.84	2.76	3.70	1.42	2.02	5.51
42.4	2.6	2.55	3.25	1087	6.46	3.05	4.12	1.41	1.99	6.10
42.4	2.9	2.83	3.60	1052	7.06	3.33	4.53	1.40	1.96	6.66
42.4	3.2	3.09	3.94	1018	7.62	3.59	4.93	1.39	1.93	7.19
42.4	3.6	3.45	4.39	973	8.33	3.93	5.44	1.38	1.90	7.86
48.3	1.6	1.84	2.35	1598	6.41	2.65	3.49	1.65	2.73	5.31
48.3	1.8	2.06	2.63	1569	7.12	2.95	3.89	1.65	2.71	5.89
48.3	2.0	2.28	2.91	1541	7.81	3.23	4.29	1.64	2.68	6.47
48.3	2.3	2.61	3.32	1500	8.81	3.65	4.87	1.63	2.65	7.30
48.3	2.6	2.93	3.73	1459	9.78	4.05	5.44	1.62	2.62	8.10
48.3	2.9	3.25	4.14	1419	10.70	4.43	5.99	1.61	2.59	8.86
48.3	3.2	3.56	4.53	1379	11.59	4.80	6.52	1.60	2.56	9.59
48.3	3.6	3.97	5.06	1327	12.71	5.26	7.21	1.59	2.51	10.52
48.3	4.0	4.37	5.57	1276	13.77	5.70	7.87	1.57	2.47	11.40
48.3	4.5	4.86	6.19	1213	15.01	6.21	8.66	1.56	2.42	12.43
48.3	5.0	5.34	6.80	1152	16.15	6.69	9.42	1.54	2.37	13.38
48.3	6.0	6.26	7.97	1035	18.19	7.53	10.81	1.51	2.28	15.07

CIRCULAR SIZE RANGE

CIRCULAR HOLLOW SECTION IS:1161 : 2014

Outside Diameter	Thickness	Mass	Area of Cross Section	Internal Volume	Moment of Inertia	Elastic Modulus	Plastic Modulus	Radius of Gyration	Square of Radius of Gyration	Torsional Constant
mm	mm	kg/m	cm ²	cm ³ /m	cm ⁴	cm ³	cm ³	cm	cm ²	cm ³
48.3	8.0	7.95	10.13	819	21.37	8.85	13.16	1.45	2.11	17.70
60.3	1.6	2.32	2.95	2561	12.72	4.22	5.51	2.08	4.31	8.44
60.3	2.0	2.88	3.66	2489	15.58	5.17	6.80	2.06	4.25	10.34
60.3	2.3	3.29	4.19	2437	17.65	5.85	7.74	2.05	4.21	11.71
60.3	2.6	3.70	4.71	2384	19.65	6.52	8.66	2.04	4.17	13.04
60.3	2.9	4.11	5.23	2333	21.59	7.16	9.56	2.03	4.13	14.32
60.3	3.2	4.51	5.74	2282	23.47	7.78	10.44	2.02	4.09	15.57
60.3	3.6	5.03	6.41	2215	25.87	8.58	11.59	2.01	4.03	17.16
60.3	4.0	5.55	7.07	2148	28.17	9.34	12.70	2.00	3.98	18.69
60.3	4.5	6.19	7.89	2067	30.90	10.25	14.04	1.98	3.92	20.50
60.3	5.0	6.82	8.69	1987	33.48	11.10	15.33	1.96	3.85	22.21
60.3	6.0	8.04	10.24	1832	38.18	12.66	17.76	1.93	3.73	25.33
60.3	8.0	10.32	13.14	1541	45.99	15.25	22.05	1.87	3.50	30.51
71.5	3.2	5.39	6.87	3329	40.13	11.22	14.94	2.42	5.84	22.45
71.5	3.6	6.03	7.68	3247	44.38	12.41	16.61	2.40	5.78	24.83
71.5	4.0	6.66	8.48	3167	48.48	13.56	18.25	2.39	5.72	27.12
71.5	5.0	8.20	10.45	2971	58.07	16.24	22.15	2.36	5.56	32.49
71.5	6.0	9.69	12.35	2781	66.77	18.68	25.81	2.33	5.41	37.35
71.5	8.0	12.53	15.96	2419	81.72	22.86	32.43	2.26	5.12	45.72
76.2	2.0	3.66	4.66	4094	32.11	8.43	11.01	2.62	6.89	16.85
76.2	2.3	4.19	5.34	4026	36.49	9.58	12.56	2.61	6.83	19.15
76.2	2.6	4.72	6.01	3959	40.76	10.70	14.09	2.60	6.78	21.40
76.2	2.9	5.24	6.68	3893	44.92	11.79	15.59	2.59	6.73	23.58
76.2	3.2	5.76	7.34	3826	48.98	12.86	17.06	2.58	6.67	25.71
76.2	3.6	6.45	8.21	3739	54.23	14.23	18.99	2.57	6.60	28.47
76.2	4.0	7.12	9.07	3653	59.30	15.56	20.87	2.56	6.54	31.13
76.2	4.5	7.96	10.14	3547	65.39	17.16	23.16	2.54	6.45	34.33
76.2	5.0	8.78	11.18	3442	71.22	18.69	25.39	2.52	6.37	37.39
76.2	6.0	10.39	13.23	3237	82.11	21.55	29.64	2.49	6.21	43.10
76.2	8.0	13.46	17.14	2846	101.03	26.52	37.38	2.43	5.89	53.03
88.9	2.0	4.29	5.46	5661	51.57	11.60	15.11	3.07	9.44	23.20
88.9	2.3	4.91	6.26	5581	58.70	13.21	17.25	3.06	9.38	26.41
88.9	2.6	5.53	7.05	5502	65.68	14.78	19.37	3.05	9.32	29.55
88.9	2.9	6.15	7.84	5424	72.52	16.31	21.46	3.04	9.26	32.63
88.9	3.2	6.76	8.62	5346	79.21	17.82	23.51	3.03	9.19	35.64
88.9	3.6	7.57	9.65	5242	87.90	19.77	26.21	3.02	9.11	39.55
88.9	4.0	8.38	10.67	5140	96.34	21.67	28.85	3.00	9.03	43.35
88.9	4.5	9.37	11.93	5014	106.54	23.97	32.09	2.99	8.93	47.94
88.9	5.0	10.35	13.18	4889	116.37	26.18	35.24	2.97	8.83	52.36
88.9	6.0	12.27	15.63	4645	134.94	30.36	41.31	2.94	8.64	60.72
88.9	8.0	15.96	20.33	4174	167.97	37.79	52.53	2.87	8.26	75.58
88.9	10.0	19.46	24.79	3728	195.98	44.09	62.59	2.81	7.91	88.18
88.9	5.0	10.35	13.18	4889	116.37	26.18	35.24	2.97	8.83	52.36
101.6	2.0	4.91	6.26	7482	77.63	15.28	19.84	3.52	12.41	30.56
101.6	2.3	5.63	7.18	7390	88.48	17.42	22.68	3.51	12.33	34.84
101.6	2.6	6.35	8.09	7299	99.14	19.52	25.49	3.50	12.26	39.03
101.6	2.9	7.06	8.99	7208	109.59	21.57	28.26	3.49	12.19	43.15

CIRCULAR HOLLOW SECTION IS:1161 : 2014

Outside Diameter	Thickness	Mass	Area of Cross Section	Internal Volume	Moment of Inertia	Elastic Modulus	Plastic Modulus	Radius of Gyration	Square of Radius of Gyration	Torsional Constant
mm	mm	kg/m	cm ²	cm ³ /m	cm ⁴	cm ³	cm ³	cm	cm ²	cm ³
101.6	3.2	7.77	9.89	7118	119.85	23.59	31.00	3.48	12.12	47.19
101.6	3.6	8.70	11.08	6999	133.24	26.23	34.59	3.47	12.02	52.46
101.6	4.0	9.63	12.26	6881	146.28	28.80	38.12	3.45	11.93	57.59
101.6	4.5	10.78	13.73	6735	162.13	31.92	42.46	3.44	11.81	63.83
101.6	5.0	11.91	15.17	6590	177.47	34.93	46.70	3.42	11.70	69.87
114.3	2.0	5.54	7.06	9555	111.27	19.47	25.23	3.97	15.77	38.94
114.3	2.3	6.35	8.09	9452	126.95	22.21	28.86	3.96	15.69	44.43
114.3	2.6	7.16	9.12	9348	142.37	24.91	32.45	3.95	15.60	49.82
114.3	2.9	7.97	10.15	9246	157.55	27.57	36.00	3.94	15.52	55.13
114.3	3.2	8.77	11.17	9144	172.47	30.18	39.51	3.93	15.44	60.36
114.3	3.6	9.83	12.52	9009	191.98	33.59	44.13	3.92	15.33	67.19
114.3	4.0	10.88	13.86	8875	211.07	36.93	48.69	3.90	15.23	73.86
114.3	4.5	12.19	15.52	8709	234.32	41.00	54.28	3.89	15.10	82.00
114.3	5.0	13.48	17.17	8544	256.92	44.96	59.77	3.87	14.96	89.91
114.3	6.0	16.03	20.41	8219	300.21	52.53	70.45	3.83	14.71	105.06
127.0	2.6	7.98	10.16	11652	196.65	30.97	40.24	4.40	19.35	61.94
127.0	2.9	8.88	11.31	11537	217.78	34.30	44.67	4.39	19.26	68.59
127.0	3.2	9.77	12.45	11423	238.60	37.57	49.06	4.38	19.17	75.15
127.0	3.6	10.96	13.96	11272	265.87	41.87	54.83	4.36	19.05	83.74
127.0	4.0	12.14	15.46	11122	292.61	46.08	60.54	4.35	18.93	92.16
127.0	4.5	13.60	17.32	10936	325.29	51.23	67.56	4.33	18.78	102.45
127.0	5.0	15.05	19.16	10751	357.14	56.24	74.46	4.32	18.64	112.48
127.0	6.0	17.91	22.81	10387	418.44	65.90	87.92	4.28	18.35	131.79
139.7	2.6	8.79	11.20	14208	263.21	37.68	48.88	4.85	23.50	75.36
139.7	2.9	9.79	12.46	14082	291.68	41.76	54.28	4.84	23.40	83.52
139.7	3.2	10.77	13.72	13956	319.78	45.78	59.63	4.83	23.30	91.56
139.7	3.6	12.09	15.39	13789	356.65	51.06	66.70	4.81	23.17	102.12
139.7	4.0	13.39	17.05	13623	392.86	56.24	73.68	4.80	23.04	112.49
139.7	4.5	15.01	19.11	13417	437.20	62.59	82.29	4.78	22.87	125.18
139.7	5.0	16.61	21.16	13212	480.54	68.80	90.76	4.77	22.71	137.59
139.7	6.0	19.79	25.20	12808	564.26	80.78	107.33	4.73	22.39	161.56
139.7	8.0	25.99	33.10	12018	720.29	103.12	138.93	4.66	21.76	206.24
165.1	2.6	10.42	13.27	20081	438.23	53.09	68.66	5.75	33.02	106.17
165.1	2.9	11.60	14.78	19931	486.13	58.89	76.30	5.74	32.90	117.78
165.1	3.2	12.78	16.28	19781	533.48	64.63	83.89	5.73	32.78	129.25
165.1	3.6	14.34	18.27	19582	595.79	72.17	93.91	5.71	32.62	144.35
165.1	4.0	15.89	20.24	19384	657.16	79.61	103.83	5.70	32.46	159.22
165.1	4.5	17.83	22.70	19138	732.57	88.74	116.10	5.68	32.27	177.49
165.1	5.0	19.75	25.15	18894	806.54	97.70	128.20	5.66	32.07	195.41
165.1	6.0	23.55	29.99	18409	950.25	115.11	151.95	5.63	31.69	230.22
165.1	8.0	31.00	39.48	17460	1221.25	147.94	197.61	5.56	30.93	295.88
168.3	2.6	10.63	13.53	20893	464.63	55.21	71.39	5.86	34.33	110.43
168.3	2.9	11.83	15.07	20739	515.46	61.26	79.34	5.85	34.21	122.51
168.3	3.2	13.03	16.60	20587	565.74	67.23	87.24	5.84	34.09	134.46
168.3	3.6	14.63	18.63	20384	631.90	75.09	97.67	5.82	33.92	150.18
168.3	4.0	16.21	20.65	20182	697.09	82.84	108.00	5.81	33.76	165.68
168.3	4.5	18.18	23.16	19931	777.22	92.36	120.77	5.79	33.56	184.72

CIRCULAR SIZE RANGE

CIRCULAR SIZE RANGE

CIRCULAR HOLLOW SECTION IS:1161 : 2014

Outside Diameter	Thickness	Mass	Area of Cross Section	Internal Volume	Moment of Inertia	Elastic Modulus	Plastic Modulus	Radius of Gyration	Square of Radius of Gyration	Torsional Constant
mm	mm	kg/m	cm ²	cm ³ /m	cm ⁴	cm ³	cm ³	cm	cm ²	cm ³
168.3	5.0	20.14	25.65	19681	855.85	101.70	133.38	5.78	33.36	203.41
168.3	6.0	24.02	30.59	19187	1008.69	119.87	158.12	5.74	32.97	239.74
168.3	8.0	31.63	40.29	18218	1297.27	154.16	205.74	5.67	32.20	308.32
193.7	2.6	12.26	15.61	27907	712.68	73.59	94.96	6.76	45.66	147.17
193.7	2.9	13.65	17.38	27730	791.21	81.69	105.58	6.75	45.52	163.39
193.7	3.2	15.04	19.15	27553	869.00	89.73	116.14	6.74	45.38	179.45
193.7	3.6	16.88	21.50	27318	971.55	100.31	130.11	6.72	45.19	200.63
193.7	4.0	18.72	23.84	27084	1072.79	110.77	143.97	6.71	45.00	221.54
193.7	4.5	21.00	26.75	26793	1197.52	123.65	161.12	6.69	44.77	247.29
193.7	5.0	23.27	29.64	26504	1320.23	136.32	178.08	6.67	44.54	272.63
193.7	6.0	27.78	35.38	25930	1559.72	161.05	211.46	6.64	44.08	322.09
193.7	8.0	36.64	46.67	24801	2015.54	208.11	276.05	6.57	43.19	416.22
219.7	2.6	13.92	17.73	36136	1044.90	95.12	122.55	7.68	58.92	190.24
219.7	2.9	15.51	19.75	35934	1160.68	105.66	136.31	7.67	58.76	211.32
219.7	3.2	17.09	21.76	35733	1275.49	116.11	150.00	7.66	58.60	232.22
219.7	3.6	19.19	24.44	35466	1427.08	129.91	168.13	7.64	58.39	259.82
219.7	4.0	21.28	27.11	35199	1576.96	143.56	186.13	7.63	58.18	287.11
219.7	5.0	26.48	33.72	34537	1944.29	177.00	230.52	7.59	57.65	353.99
219.7	6.0	31.63	40.28	33882	2301.27	209.49	274.08	7.56	57.13	418.98
219.7	8.0	41.77	53.21	32589	2984.92	271.73	358.71	7.49	56.10	543.45
219.7	10.0	51.72	65.88	31322	3629.46	330.40	440.07	7.42	55.09	660.80
254.0	4.0	24.67	31.42	47529	2455.00	193.31	250.02	8.84	78.15	386.61
254.0	5.0	30.71	39.11	46759	3032.52	238.78	310.05	8.81	77.53	477.56
254.0	6.0	36.70	46.75	45996	3596.01	283.15	369.10	8.77	76.93	566.30
254.0	8.0	48.54	61.83	44488	4681.82	368.65	484.30	8.70	75.73	737.29
254.0	10.0	60.19	76.65	43005	5714.24	449.94	595.69	8.63	74.55	899.88
273.1	5.0	33.06	42.11	54367	3785.05	277.19	359.43	9.48	89.88	554.38
273.1	6.0	39.53	50.35	53543	4492.13	328.97	428.13	9.45	89.22	657.95
273.1	8.0	52.31	66.63	51915	5858.34	429.03	562.39	9.38	87.93	858.05
273.1	10.0	64.90	82.66	50312	7162.25	524.51	692.55	9.31	86.65	1049.03
273.1	12.0	77.28	98.43	48735	8405.78	615.58	818.65	9.24	85.40	1231.17
323.9	5.0	39.33	50.09	77388	6369.42	393.30	508.53	11.28	127.15	786.59
323.9	6.0	47.05	59.92	76405	7572.47	467.58	606.43	11.24	126.37	935.16
323.9	8.0	62.34	79.39	74458	9910.08	611.92	798.51	11.17	124.82	1223.84
323.9	10.0	77.43	98.61	72536	12158.34	750.75	985.67	11.10	123.29	1501.49
323.9	12.0	92.32	117.58	70639	14319.56	884.20	1167.96	11.04	121.78	1768.39
355.6	6.0	51.74	65.90	92725	10070.55	566.40	733.39	12.36	152.82	1132.80
355.6	8.0	68.59	87.36	90579	13201.37	742.48	966.78	12.29	151.11	1484.97
355.6	10.0	85.25	108.57	88457	16223.50	912.46	1194.73	12.22	149.42	1824.92

CIRCULAR SIZE RANGE

CIRCULAR HOLLOW SECTION IS:1161 : 2014

Outside Diameter	Thickness	Mass	Area of Cross Section	Internal Volume	Moment of Inertia	Elastic Modulus	Plastic Modulus	Radius of Gyration	Square of Radius of Gyration	Torsional Constant
mm	mm	kg/m	cm ²	cm ³ /m	cm ⁴	cm ³	cm ³	cm	cm ²	cm ³
355.6	12.0	101.70	129.53	86361	19139.47	1076.46	1417.31	12.16	147.76	2152.92
377.0	6.0	54.91	69.93	104635	12035.01	638.46	825.92	13.12	172.10	1276.92
377.0	8.0	72.81	92.74	102354	15791.85	837.76	1089.46	13.05	170.28	1675.53
377.0	10.0	90.52	115.30	100098	19425.87	1030.55	1347.22	12.98	168.49	2061.10
377.0	12.0	108.04	137.60	97868	22939.76	1216.96	1599.28	12.91	166.71	2433.93
406.4	6.0	59.26	75.47	122170	15128.33	744.50	961.99	14.16	200.45	1489.01
406.4	8.0	78.62	100.13	119704	19873.89	978.05	1269.95	14.09	198.48	1956.09
406.4	10.0	97.78	124.53	117264	24475.81	1204.52	1571.66	14.02	196.54	2409.04
406.4	12.0	116.74	148.69	114849	28937.01	1424.07	1867.19	13.95	194.62	2848.13

CIRCULAR SIZE RANGE

CHS (Circular Hollow Section) Sizes

SIZE	1.6	1.8	2.0	2.3	2.6	2.9	3.2	3.6	4.0	4.5	5.0	6.0	8.0	10.0	12.0
21.3	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
26.4	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
33.7	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
42.4	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
48.3	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
60.3	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
76.2	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
88.9	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
101.6	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
114.3	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
127	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
139.7	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
152.4	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
165.1	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
168.3	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
193.7	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
219.1	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
254.0	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
273.1	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
323.9	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
355.6	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
377.0	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
406.4	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

CIRCULAR SIZE RANGE

Contact Details:

Mr. Rohit Kapur - T +91 9818739556 | Mr. Vikas Arya - T +91 9667792719

Mr. Hemant Vashishtha - T +91 8130007521



Scan to know more about us



Head Office:

36, Kaushambi, Near Anand Vihar Terminal, Delhi (NCR) 201010, India.
T +91-120 4041400 F +91-120 4041444

Corporate Office:

Tapasya Corp Heights, 4th Floor, Tower A, Sector 126, Noida, Uttar Pradesh - 201303, India
T +91-120-4742700/701

Contact Details:

Mr. Rohit Kapur - T +91 9818739556 | Mr. Vikas Arya - T +91 9667792719
Mr. Hemant Vashishtha - T +91 8130007521

STAY CONNECTED. STAY UPDATED.

[f](#) [in](#) [t](#) [v](#) / APL APOLLO [@](#) / APL APOLLO OFFICIAL | CUSTOMER CARE: 1800-102-3737

info@aplapollo.com | www.aplapollo.com